

New Stock - Siemens

Quantity Stocked	Description	Part Number
9	3RH1921-ICA10	3RH1921-ICA10
4	AUXIL. SWITCH 1NO+1NC (ACCESSORY FOR SWITCH 3LD2) -NEW DESIGN - FOR FLOOR MOUNTING FOR INSTALLATION IN DISTR. BOARDS AND INSULATED ENCLOSURE	3LD9200-5C
6	CIRCUIT-BREAKER 36...45 A, N-RELEASE 585 A, SIZE S2, MOTOR PROTECTION CLASS 10 SCREW CONNECTION STANDARD BREAKING CAPACITY	3RV1031-4GA10
1	COMMUNICATION MODULE CM 1242-5; FOR CONNECTION OF SIMATIC S7-1200 TO PROFIBUS AS DP SLAVE MODULE	6GK7242-5DX30-0XE0
2	CONNECTION CABLE; LENGTH 0,1M; FLAT; CONNECTION OF BASIC UNIT TO CURRENT MEASURING MODULE, CURRENT/VOLTAGE MEASUR. MODULE, OPERATOR PANEL OR TO EXPANSION MODULES VIA SYSTEM INTERFACE	3UF7931-0AA00-0
1	FRONT CONNECTOR WITH TWISTED RIBBON CABLE CONNECTION FOR ANALOG (40PINS) S7-300 MODULES, POWER SUPPLY USING SCREW-TYPE TERMINALS	6ES7921-3AG20-0AA0
1	LOGO! 12/24RCE, logic module, disp PS/I/O: 12/24VDC/relay, 8 DI (4AI)/4DO, memory 400 blocks, modular expandable, Ethernet, integr. web server, data log, user-defined Web pages, standard microSD card for LOGO! Soft Comfort V8 or higher, older project	6ED1052-1MD08-0BA0
1	OPERATOR PANEL OP7/PP LC DISPLAY, BACKLIT LED 4 LINES, 20 CHARACTERS/LINE, SIMATIC S5, 505,NATIVE DRIVERS, UL/CSA-LISTED	6AV3607-1JC00-0AX1
1	OVERLOAD RELAY 12.5...50 A FOR MOTOR PROTECTION SIZE S2, CLASS 10 STAND-ALONE INSTALLATION MAIN CIRCUIT: THROUGH TRANSF. AUX. CIRCUIT: SCREW CONNECTION MANUAL-AUTOMATIC-RESET	3RB2036-1UW1
1	S7-300 CONNECTING CABLE FOR 64 CHANNEL MODULES, LENGTH: 1M 2 PIECES PER PACKAGING UNIT	6ES7392-4BB00-0AA0
1	SHUNT TRIP AC 210...240V,50/60HZ, 100% ED, DC 190...330V, 5SEC ED, AC 190...330V,50/60HZ, 5SEC ED, FOR S00...S3,	3RV1902-1DP0
1	SIMATIC DP, BUS UNIT FOR ET200M F. THE INTEGR.OF TWO 40 MM WIDE I/O SUBMODULES FOR INSERT/REMOVE	6ES7195-7HB00-0XA0
1	SIMATIC HMI KTP600 BASIC COLOR DP, BASIC PANEL, KEY AND TOUCH OPERATION, 6" TFT DISPLAY, 256 COLORS, MPI/PROFIBUS DP INTERFACE, CONFIGURATION FROM WINCC FLEXIBLE 2008 SP2 COMPACT/ WINCC BASIC V11/ STEP7 BASIC V11, CONTAINS OPEN SOURCE SW WHICH IS PROVIDED	6AV6647-0AC11-3AX0
1	SIMATIC NET INDUSTRIAL ETHERNET TP CORD RJ45/RJ45, CAT 6A, TP CABLE 4X2, PREASSEMBLED W. W. 2 RJ45 CONNECTORS, L = 0.5 M	6XV1870-3QE50
3	SIMATIC S5 375 MEMORY SUBMODULE EPROM, 8K BYTES	6ES5375-0LA15
1	SIMATIC S7, BACKUP BATTERY (LI) 3.6V/MIN. 0.85AH, FOR FOR S7-300 CPUS AND S5-90U	6ES7971-1AA00-0AA0
1	SIMATIC S7, MEMORY CARD FOR S7-300, SHORT VERSION, 5V FLASH EPROM, 128 KBYTES	6ES7951-0KG00-0AA0
1	SIMATIC S7-1200, DIGITAL INPUT SM 1221, 16 DI, 24VDC, SINK/SOURCE INPUT	6ES7221-1BH30-0XB0
4	SIMATIC S7-1200, DIGITAL OUTPUT SM 1222, 16 DO, 24V DC, TRANSISTOR 0.5A	6ES7222-1BH30-0XB0
1	SIMATIC S7-300, ANALOG OUTPUT SM 332, OPTICALLY ISOLATED, 4 AO, U/I; DIAGNOSTICS; RESOLUTION 11/12 BITS, 20 PIN, REMOVE/INSERT W. ACTIVE, BACKPLANE BUS	6ES7332-5HD01-0AB0
1	SIMATIC S7-300, CONNECTING CABLE BETWEEN IM 360/IM 361 LENGTH: 1M	6ES7368-3BB01-0AA0
1	SIMATIC S7-300, CP 340 COMMUNICATION PROCESSOR WITH RS232C INTERFACE (V.24) INCL. CONFIG. PACKAGE ON CD	6ES7340-1AH02-0AE0
1	SIMATIC S7-300, CPU 315-2DP CPU WITH MPI INTERFACE INTEGRATED 24 V DC POWER SUPPLY 128 KBYTE WORKING MEMORY 2. INTERFACE DP-MASTER/SLAVE MICRO MEMORY CARD NECESSARY	6ES7315-2AG10-0AB0
1	SIMATIC S7-300, CPU 316-2DP CPU WITH INTEGRATED 24 V DC POWER SUPPLY, 128 KBYTE WORKING MEMORY 2ND INTERF. DP-MASTER/SLAVE	6ES7316-2AG00-0AB0
2	SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED 16DO, RELAY CONTACTS, 1 X 20 PIN	6ES7322-1HH01-0AA0
1	SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED, 16 DO, 24V DC, 0.5A, 1 X 20 PIN SUM OF OUTPUT CURRENTS 4A/GROUP (8A/MODULE)	6ES7322-1BH01-0AA0
1	SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED, 8 DO (RELAY), 1 X 40 PIN, 24V DC, 5A OR 230V AC, 5A, CONNECTOR W. SPRING TERMINAL CAN BE USED FROM 6ES7392-1BM01-0AA0	6ES7322-1HF10-0AA0
4	TERMINAL BLOCK TPA 3-TIER FOR ANALOG SIMATIC S7 MODULES SORT: SCREW TERMINAL WITHOUT LED, PACK. UNIT=1 PCS 16 POLE IDC CONNECT. FOR CABLE	6ES7924-0CC10-0AA0
5	THERMAL.DELAYED OVERLOAD RELAY F.MOUNTG.ONTO CONTACT./STARTERS SETTING RANGE 1 TO 1.6A 1NO+1NC	3UA5000-1A
7	COMPLETE UNIT 22MM F. 1 CONTACT PUSHBT.UNIT W. FLAT PUSHBUTTON BLACK, 1NO WITH METAL FRONT RING	3SB1202-0AB20